

08/876117



06/13/97

G11C27/008

(54) WRITE-IN CIRCUIT FOR NON-VOLATILE ANALOG MEMORY

(11) 57-176598 (A) (43) 29.10.1982 (19) JP


(21) Appl. No. 56-60247 (22) 20.4.1981

(71) SANYO DENKI K.K. (72) MINORU HAMADA

(51) Int. Cl. G11C27/00, G11C17/00

PURPOSE: To decrease the time required for write of an analog signal by comparing a threshold voltage of an analog memory with a reference voltage and generating a write-in pulse with a peak value in response to the magnitude of the difference.

CONSTITUTION: When a difference between a threshold voltage of a non-volatile analog memory NVAM and a reference voltage V_s detected at a threshold value detecting circuit 20 becomes greater, a voltage outputted from a voltage control circuit 21 is quickly increased and the peak value of write-in pulse generated from a write-in pulse generating circuit 22 is quickly increased by the increase. As a result, the threshold voltage of the NVAM is rapidly closed to the objective value. On the other hand, when the threshold voltage of the NVAM closes to a desired value and the difference with the voltage V_s becomes smaller, the increment of the write-in pulse is decreased, allowing to adjust the threshold value of the NVAM minutely. When the both are coincident, the circuit 20 gives an inhibiting signal V_y to the circuit 22 to complete the write-in operation.



DOC.

P11C27/008